



**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	862.C1951
First Named Inventor or Application Identifier	
HIDEYUKI MAKITANI	
Express Mail Label No.	

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☐ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification Total Pages **41**
3. ☒ Drawing(s) (35 USC 113) Total Sheets **08**
4. ☒ Oath or Declaration Total Pages **01**
- a. ☐ Newly executed (original or copy)
- b. ☒ Unexecuted for information purposes
- c. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
- i. ☐ **DELETION OF INVENTOR(S)**
Signed Statement attached deleting
inventor(s) named in the prior application, see
37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4c is checked)
The entire disclosure of the prior application, from which a copy of
the oath or declaration is supplied under Box 4c, is considered as
being part of the disclosure of the accompanying application and is
hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement
(when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure
Statement (IDS)/PTO-1449 ☐ Copies of IDS
Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other: _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label **05514** (Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

NAME				
Address				
City		State		Zip Code
Country		Telephone		Fax

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	20-20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	5-3 =	2	X \$ 78.00 =	\$156.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$ 0.00
				BASIC FEE (37 CFR 1.16(a))	\$690.00
			Total of above Calculations = \$846.00		
Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).					
TOTAL = \$846.00					

19. Small entity status


- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$846.00 to cover the filing fee is enclosed.21. ☐ A check in the amount of \$_____ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge any deficiencies in the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME	JOSEPH W. RAGUSA, Reg. No. 38,586
SIGNATURE	
DATE	July 6, 2000

0961867-1 070700

0961867-1 070700

0961867-1 070700

0961867-1 070700

0961867-1 070700

0961867-1 070700

0961867-1 070700

002020122290

communication controller, it is possible to use a FIFO buffer to reduce the frequency with which CPU interrupt occurs, though often the communication controller that is incorporated within a low-cost single-chip

5 microcontroller does not come equipped with this function. A microcontroller that is available can perform data transfer without the intervention of a CPU by using a combination of a DMA controller and a communication controller. However, since the length of
10 received messages is indeterminate, the DMA transfer length cannot be set in advance. This necessitates an operation in which a CPU polls the counter of the DMA controller. Such a microcontroller, therefore, is not suitable for receiving variable-length messages as is.

15 Meanwhile, there is a tendency for the amount of data transferred between devices to increase as functions become more sophisticated. For example, when the image processing speed of an image input/output unit rises, communication time allowed for control between
20 pages tends to shorten. Hence there is a demand for ever higher data communication speed.

SUMMARY OF THE INVENTION

25 Accordingly, an object of the present invention is to provide a method and system for data communication

00612571 070700

between devices, wherein by adopting a scheme in which a variable-length message is transferred upon being divided into fixed-length packets, it is possible to combine and control a DMA controller and a communication
5 controller, thereby achieving high-speed data communication, even in a low-cost single-chip microcomputer.

According to the present invention, the foregoing object is attained by providing an image processing
10 system comprising a combination of an image control unit and one or a plurality of image input/output units, wherein the image input/output unit and the image control unit are connected by communication means, the image control unit has first communication control means
15 connected to the communication means, the image input/output unit has second communication control means connected to the communication means, and the system further includes control means for performing control so as to set predetermined communication conditions in the
20 first and second communication control means at initialization, decide fixed packet length based upon mutually communicable packet lengths of packets exchanged via the communication means, set the decided fixed packet length in the first and second
25 communication control means anew, and continue subsequent communication by DMA transfer in which a data

string is divided into the set fixed packet lengths.

In a case where the data string is a variable-length message, the control means performs control in such a manner that a transmitting side adds information indicative of the end of a message onto a final packet when the variable-length message is transmitted upon being divided into fixed-length packets, and a receiving side reproduces the original variable-length message after recognizing added-on final-packet information.

Further, the control means includes first control means in the image control unit for controlling the first communication control means, and second control means in the image input/output unit for controlling the second communication control means. Further, the decision of the fixed packet length is made by the first control means. Further, the decision of the fixed packet length is made by the second control means. Further, the fixed packet length decided upon is whichever of the packet lengths of respective ones of the first and second communication control means is smaller than an upper-limit value. Further, an image reading unit is connected as the image input/output unit and the system operates as an image reading system. Further, an image forming unit is connected as the image input/output unit and the system functions as an image forming system. Further, an image reading unit and an image forming unit

00612571-070700

are connected as the image input/output units and the system functions as an image input/output system. Further, start-stop synchronization serial communication means is used as the communication means, a serial
5 communication controller and a DMA controller are combined as the communication control means, the DMA controller transfers data by the fixed-length packets in accordance with a data transfer request from the serial communication controller and interrupts the image
10 control unit when transfer of the fixed-length packet is completed.

Further, the present invention provides a system constructed by combining a plurality of devices and connecting them by communication means, wherein a first
15 device has first communication control means connected to the communication means, a second device has second communication control means connected to the communication means, and the system further includes control means for performing control so as to set
20 predetermined communication conditions in the first and second communication control means at initialization, decide fixed packet length based upon mutually communicable packet lengths of packets exchanged via the communication means, set the decided fixed packet length
25 in the first and second communication control means anew, and continue subsequent communication.

09612571.070700

In a case where a data string is a variable-length message, the control means performs control in such a manner that a transmitting side adds information indicative of the end of a message onto a final packet

5 when the variable-length message is transmitted upon being divided into fixed-length packets, and a receiving side reproduces the original variable-length message after recognizing added-on final-packet information.

Further, the present invention provides a data

10 communication method in an image processing system comprising a combination of an image control unit and one or a plurality of image input/output units, the image input/output unit and the image control unit being connected by communication means, wherein in a case

15 where the image control unit has first communication control means connected to the communication means and the image input/output unit has second communication control means connected to the communication means, the method comprises an initial communication conditions

20 setting step of setting predetermined communication conditions in the first and second communication control means at initialization; a fixed packet length deciding step of deciding fixed packet length based upon mutually communicable packet lengths of packets exchanged via the

25 communication means; and a fixed packet length setting step of setting the decided fixed packet length in the

09612571.070700

first and second communication control means anew and continuing subsequent communication by DMA transfer in which a data string is divided into the set fixed packet lengths.

5 In the fixed-packet length deciding step, the fixed packet length decided upon is whichever of the packet lengths of respective ones of the first and second communication control means is smaller than an upper-limit value. Further, after the fixed packet length has
10 been set anew, communication is resumed upon elapse of a predetermined period of time. Further, start-stop synchronization serial communication means is used as the communication means, a serial communication
15 controller and a DMA controller are combined as the communication control means, the DMA controller transfers data in the fixed-length packet in accordance with a data transfer request from the serial
20 communication controller and interrupts the image control unit when transfer of the fixed-length packet is completed.

 Further, the present invention provides a data communication method in a system constructed by combining a plurality of devices and connecting them by communication means, wherein in a case a first device
25 has first communication control means connected to the communication means and a second device has second

communication control means connected to the
communication means, the method comprises the steps of:
setting predetermined communication conditions in the
first and second communication control means at
5 initialization; deciding fixed packet length based upon
mutually communicable packet lengths of packets
exchanged via the communication means; and setting the
decided fixed packet length in the first and second
communication control means anew and continuing
10 subsequent communication.

In a case where a data string is a variable-length
message, a transmitting side adds information indicative
of the end of a message onto a final packet when the
variable-length message is transmitted upon being
15 divided into fixed-length packets, and a receiving side
reproduces the original variable-length message after
recognizing added-on final-packet information.

Further, the present invention provides a storage
medium storing a computer-readable communication control
20 program of an image processing system comprising a
combination of an image control unit and one or a
plurality of image input/output units, the image
input/output unit and the image control unit being
connected by communication means, wherein in a case
25 where the image control unit has first communication
control means connected to the communication means and

the image input/output unit has second communication control means connected to the communication means, the communication control program includes an initial communication conditions setting step of setting

5 predetermined communication conditions in the first and second communication control means at initialization; a fixed packet length deciding step of deciding fixed packet length based upon mutually communicable packet lengths of packets exchanged via the communication

10 means; and a fixed packet length setting step of setting the decided fixed packet length in the first and second communication control means anew and continuing subsequent communication by DMA transfer in which a data string is divided into the set fixed packet lengths.

15 The communication control program includes a program in the image control unit executed by a first control unit for controlling the first communication control means, and a program in the image input/output unit executed by a second control unit for controlling

20 the second communication control means.

Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate

25 the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating an example
5 of the control components of an image input/output
system according to an embodiment of the present
invention;

Fig. 2 is a sectional view showing an example of
the configuration of the image input/output system
10 according to this embodiment;

Fig. 3 is a block diagram showing an example of the
construction of a controller according to this
embodiment;

Fig. 4 is a block diagram showing an example of the
15 construction of a reader according to this embodiment;

Fig. 5 is a block diagram illustrating a detailed
arrangement relating to communication control in the
reader according to this embodiment;

Figs. 6A and 6B are flowcharts illustrating an
20 example of processing for deciding communication
conditions according to this embodiment;

Figs. 7A and 7B are flowcharts illustrating an
example of processing for sending and receiving messages
according to this embodiment; and

09642571.070700

A printer (image output unit) 300 transports printing paper, prints image data on the printing paper in the form of a visible image and discharges the paper to the exterior of the apparatus. The printer 300 is constituted primarily by a paper feed unit 310 having printing paper cassettes of a plurality of types, a marking unit 320 having a function for transferring image data to printing paper and fixing the image on the paper, and a paper discharge unit 330 having a function for sorting printing paper that has been printed on, stapling the paper and outputting the stapled paper to the exterior of the apparatus.

A controller (image control unit) 110 is electrically connected to the reader 200 and printer 300 and is further connected to host computers 401 and 402 via a network 400.

The controller 110 controls the reader 200 to read in image data representing a document and controls the printer 300 to output image data to printing paper, thereby providing a copy function. The controller 110 further provides a scanner function for converting read image data from the reader 200 to code data and transmitting the code data to the host computers via the network 400, and a printer function for converting code data received from a host computer via the network 400 to image data and outputting the image data to the

printer 300.

A console 150, which is connected to the controller 110, is constituted by a liquid-crystal touch-sensitive panel to provide a user interface for operating the image input/output system.

Fig. 2 is a sectional view showing the construction of the reader 200 and printer 300.

(Example of construction of reader)

The document feeder unit 250 of the reader feeds documents to the top of a platen glass one sheet at a time in order starting from the first sheet and then discharges the documents from the platen glass 211 when the reading of the documents is completed. When a document is transported to the top of the platen glass 211, a lamp 212 is lit and an optics unit 213 is caused to start moving so that the document is exposed and scanned. Light reflected from the document at this time is introduced to a CCD image sensor (referred to as a "CCD" below) 218 by mirrors 214, 215, 216 and a lens 217. Thus, the image of the scanned document is read by the CCD 218. Image data output from the CCD 218 is subjected to predetermined processing and then transferred to the controller 110.

(Example of construction of printer)

A laser driver 321 in the printer 300 drives a laser emission unit 322. Specifically, the laser driver

09612571.070700

321 causes the laser emission unit 322 to emit laser light that conforms to the image data that has been output from the controller 110. The laser light irradiates a photosensitive drum 323 so that a latent image conforming to the laser light is formed on the drum 323. A developing unit 324 causes a developing agent to attach itself to the latent image formed on the photosensitive drum 323.

Printing paper is transported to a transfer unit 325 from a cassette 311 or 312 at a timing synchronized to the start of irradiation by the laser light, as a result of which the developing agent affixed to the photosensitive drum 323 is transferred to the printing paper. The printing paper to which the developing agent has been transferred is transported to a fixing unit 326, where the developing agent is fixed on the printing paper by heat and pressure supplied by the fixing unit 326. Upon passing through the fixing unit 326, the printing paper is ejected by ejection rollers 327. A paper discharge unit 330 gathers the discharged sheets of paper together, sorts the sheets and staples sheets that have been sorted.

If the apparatus has been set to a double-sided printing mode, the printing paper is transported up to the position of the ejection rollers 327, the rotating direction of the ejection rollers 208 is reversed and

the paper is introduced to a paper re-feed path 329 by a flapper 328. Printing paper thus reintroduced to the paper re-feed path 329 is fed to the transfer unit 325 at the above-mentioned timing.

5 (Example of construction of controller)

An example of the functions of the controller 110 will be described with reference to the block diagram of Fig. 3.

09612571.070700
A main controller 111 is constituted primarily by a
10 CPU 112, a bus controller 113 and various interface control circuits (not shown).

The CPU 112 and the bus controller 113 control the overall operation of the controller 110. The CPU 112 operates on the basis of a program read in from a ROM
15 114 via a ROM interface 115. An operation for analyzing PDL (Page Description Language) code data received from a host computer and expanding the code data into raster image data also is described in this program and is implemented by software. A bus controller 113 controls
20 the transfer of data input to and output from various interfaces, performs arbitration at the time of bus contention and controls DMA data transfer.

A DRAM 116, which is connected to the main controller 111 by a DRAM interface 117, is used as a
25 work area for operation of the CPU 112 and as a work area for storing image data. As will be described

08612571.070700

later, an arrangement may be adopted in which a program is loaded in the DRAM 116 from a host computer or external storage device (which has been connected to, e.g., an expansion connector 124) such as a floppy disk or CD, and the program is run by the CPU 112.

A codec 118 compresses raster-image data, which has been stored in the DRAM 116, by a compression scheme such as MH, MR, MMR or JBIG, etc., and expands code data, which has been compressed and stored, to raster-image data. An SRAM 119 is used as a temporary work area of the codec 118. The codec 118 is connected to the main controller 111 via an interface 120, and the transfer of data between the codec and the DRAM 116 is controlled by a bus controller 113, whereby DMA transfer is achieved.

A network controller 121 is connected to the main controller 111 by an interface 123 and is connected to an external network by a connector 122. Ethernet is an example of the external network.

The expansion connector 124 for connecting an expansion port and an input/output controller 126 are connected to a general-purpose high-speed bus 125. A PCI bus is an example of the general-purpose high-speed bus.

The input/output controller 126 is equipped with a start-stop synchronization serial communication

controller 127 in two channels for sending and receiving control commands to and from the CPUs of the reader 200 and printer 300. The start-stop synchronization serial communication controller 127 is connected to external
5 interface circuits 140, 145 by an input/output bus 128.

A panel interface 132 comprises an interface connected to an LCD controller 131 for presenting a display on the liquid-crystal screen of the console 150, and a key-input interface 130 for allowing input from
10 hard keys and keys on a touch-sensitive panel.

The console 150 has a liquid-crystal display unit, a touch-sensitive panel affixed to the liquid-crystal display unit, and a plurality of hard keys. Signals that have been entered from the touch-sensitive panel or
15 hardware keys are sent to the CPU 112 via the panel interface 132. The liquid-crystal display unit displays image data that has been sent from the panel interface 132. Functional displays for operating this image forming apparatus and displays of image data and the
20 like are presented on the liquid-crystal display unit.

A real-time clock module 133 updates/saves date and time managed within the apparatus and is backed up by a back-up battery 134.

Connectors 142 and 147 comprise start-stop
25 synchronization serial interfaces (143, 148) and video interfaces (144, 149) connected to the reader 200 and

video interface 149.

(Detailed description of reader)

A more detailed example of the functional construction of the reader will now be described with
5 reference to the block diagram of Fig. 4.

A connector 231 is connected to the connector 142 of the controller 110 and is constituted by the start-stop synchronization serial interface 233 for communication of commands between the CPU 112 and an MPU
10 228, and the video interface 234 for transferring video signals.

The MPU 228, which is a single-chip CPU for performing overall control of the scanner reader, internally incorporates the functions of a timer, a
15 DMAC, a serial communication controller (SCU) and an general-purpose input/output port, etc.

A connector 225 is connected to the document feeder unit (referred to as a "DF unit" below) 250. In order that a reading operation may be performed, the MPU 228
20 requests the DF unit 250 to feed the paper sheets of a document. In response to the request, the DF unit 250 controls an accompanying motor to implement the document-feed operation.

A CCD driver is incorporated within or connected to
25 a CCD 218 and is controlled by the MPU 228 via an I/O unit 230. Image data that has been input to the CCD 218

is photoelectrically converted to an electric signal.
The electric signal output from the CCD 218 is amplified
by an amplifier 221 and then input to an A/D converter
222. The A/D converter 222 converts the entered analog
5 electric signal to a digital signal and outputs the
digital signal. The output signal from the A/D
converter 222 enters a shading circuit 223, where non-
uniformity in distribution of light and sensitivity
unevenness of the CCD are corrected.

10 The output of the shading circuit 223 is input to a
timing generator 224 and is transferred to the
controller 110 via the connector 231 in sync with video
control signals (HYSNC/VSYNC) generated by the timing
generator 224.

15 A ROM 227 is a medium for storing the control
program of the scanner unit 210. Processing by the MPU
228 is executed based upon this program. A RAM 226 is
used as a work area when the MPU 228 executes
processing. An arrangement may be adopted in which the
20 program run by the MPU 228 is loaded into the RAM 226
from the controller 110 or from a host computer or
external storage device via the controller 110.

The communication function of the reader 200 will
now be described based upon the block diagram of Fig. 5.

25 Among the functions incorporated within the MPU
228, a CPU 240, a DMAC 241 and an SCU 242 are

09512571.070700

illustrated in the block diagram of Fig. 5. These functional blocks are connected to the RAM 226 via an address/data bus 234. A detailed description regarding the sending and receiving of data in the usual (i.e., without the intermediary of a DMAC) one-byte units is not given here as such a scheme is ordinary. What will be described in detail here is operation in which the DMAC and SCU are combined.

First, in regard to a transmitting operation, the CPU 240 sets the length of data transmitted in a channel-0 transfer-length register of the DMAC 241 and sets the leading address of the transmit data string of RAM 226 in a channel-0 address register of the DMAC 241. When a transfer-start command is applied to the SCU 242, the latter makes TRUE a transfer request TXI (246) to the DMAC 241 successively in single-byte units. The transfer request TXI is connected to a channel-0 DMA request (DREQ0; 246) of the DMAC 241. When the DMA request becomes TRUE, the DMAC 241 controls the address/data bus 243 in accordance with information that has been set and effects a data transfer from the RAM 226 to the SCU 242. The SCU 242 converts the received one byte of data to a bit sequence and outputs the bit sequence to a TXD terminal 248 in a predetermined format. When a prescribed number of transfers have been completed, the DMAC 241 makes DEND0 (244) TRUE and

notifies the CPU 240 of the end of transmission. The CPU 240 senses end of transmission by the signal on an interrupt terminal INT0 (244).

Next, in regard to a receiving operation, the CPU
5 240 sets the length of a fixed-length packet in a channel-1 transfer-length register of the DMAC 241 and sets the leading address of a receive buffer of RAM 226 in a channel-1 address register of the DMAC 241. When a bit sequence is received from an RXD terminal 249, the
10 SCU 242 converts this to byte data and then makes TRUE a transfer request RXI (247) to the DMAC 241. The RXI (247) is connected to a channel-1 DMA request (DREQ1; 247) of the DMAC 241. When the DMA request becomes TRUE, the DMAC 241 controls the address/data bus 243 in
15 accordance with information that has been set and effects a data transfer from the SCU 242 to the RAM 226. When reception of the prescribed number has been completed, the DMAC 241 makes DEND1 (245) TRUE and notifies the CPU 240 of the end of transmission. The
20 CPU 240 senses end of transmission. The CPU 240 senses end of reception by the signal on an interrupt terminal INT1 (245).

<Example of operation of system according to this embodiment>

25 Described next will be a procedure for transferring a variable-length message by a fixed-length scheme

between the image control unit and the image
input/output unit.

In this example, a procedure through which the CPU
112 (Fig. 3) of the control unit (controller) 110 and
5 the CPU 240 (Fig. 5) of the reader 200 select the fixed-
length packet scheme at the time of initialization and a
transfer procedure based upon the fixed-length packet
scheme will be described with reference to the
flowcharts shown in Figs. 6 and 7. It should be noted,
10 however, that a technical concept similar to that of the
example of Figs. 6 and 7 is applicable to determination
of communication conditions between the printer and
controller of this example and to determination of
communication conditions in a system in which a
15 plurality of devices have been connected via other
communication means. In Figs. 6A and 6B, the dashed-
line arrows between Fig. 6A and Fig. 6B indicate
communication between the reader and controller.

(Operation of reader)

20 A communication-scheme determination sequence in
the reader 200 shown in Fig. 1 will be described first
with reference to the flowchart shown in Fig. 6A.

In Fig. 6A, the RAM and various peripheral circuits
are initialized when power is applied (S601). Next, the
25 serial communication controller (SCU) 242 is initialized
according to predetermined conditions (S602). In this

embodiment, the conditions set are a baud rate of 9600 bps, data of eight bits, stop bits of two bits and odd parity. Further, the SCU 242 is configured so as to operate in direct connection with the CPU 240 without the intermediary of the DMAC 241.

Next, in order to inform the controller 110 of the fact that message reception has become possible, a CTS signal, which is a flow-control signal, is made TRUE (S603) and a message-reception standby state is attained (S604).

The reader receives a "communication negotiation start message" from the controller 110 and accepts information indicating "communication possible/impossible according to fixed-length packet scheme" and an upper-limit value (PLCmax) of the length of the fixed-length packet, which are contained in the message (step S605). In this example, the information "communication possible according to fixed-length packet scheme" and "upper-limit value of packet length is PLCmax bytes" is delivered to the reader 200 from the controller 110. The reader 200 compares this information with its own capabilities, namely whether fixed-length communication is possible/impossible and the maximum allowable value (PLRmax) of packet length and decides the final communication conditions (S606). In this example, it is decided to "perform communication

according to fixed-length packet scheme" and the smaller of PLCmax and PLRmax is adopted to decide packet length PLen. For example, if PLCmax is 16 bytes and PLRmax is 8 bytes, then 8 bytes is adopted as the packet length.

5 Next, the reader transmits the above-mentioned communication conditions to the controller 110 together with a "communication negotiation completed" message (S607).

10 If transmission of the message is completed, then reception by DMA is set in the SCU 242 and DMAC 241 (S608: set DMA transfer length to PLen bytes). This is followed by waiting for a "resume communication" message from the controller 110 (S609). When the "communication resumed" message is received from the controller 110,
15 ordinary processing is started (S610).

(Operation of controller)

Next, a communication-scheme determination sequence in the controller 110 shown in Fig. 1 will be described with reference to the flowchart shown in Fig. 6B.

20 In Fig. 6B, the RAM and various peripheral circuits are initialized when power is applied (S621). Next, the serial communication controller 127 is initialized according to predetermined conditions (S622). In this embodiment, the conditions set are a baud rate of 9600
25 bps, data of eight bits, stop bits of two bits and odd parity.

09612571.070700

Next, in order to inform the reader 200 of the fact
that message reception has become possible, an RTS
signal, which is a flow-control signal, is made TRUE
(S623) and the controller waits for the reader to attain
5 a state in which reception is possible (S624).

After it is recognized that the CTS signal has
become TRUE, the controller transmits a "communication
negotiation start message" (S625). The communication
scheme allowed by the controller is attached to this
10 message as a parameter. In this example, the
information "communication possible according to fixed-
length packet scheme" and "upper-limit value of packet
length is PLCmax bytes" is delivered.

Next, the controller awaits an answer message from
15 the reader (S626). When the "communication negotiation
completed" message is received, the communication
controller 127 is set again based upon the communication
scheme that was added on as the parameter (S627).

Next, the controller waits 100 ms for the resetting
20 of the communication conditions on the reader side and
then transmits the "resume communication" message (S629)
to start ordinary processing (S630).

(Reader transmission procedure)

A data transmission sequence according to the
25 fixed-length packet scheme in the reader 200 shown in
Fig. 1 will now be described with reference to the

09612571.070700

flowchart of Fig. 7A. In this embodiment, the procedure will be described taking a case in which PLen = 8 bytes holds as an example, an 18-byte message, for example, being transmitted upon being divided into 8-byte
5 packets.

First, an example of the data format of the packets will be described with reference to Fig. 8.

In the leading byte of each packet, message IDs are added onto the seven lower order bits and flag
10 information indicative of the final packet is added onto the most significant bit. Accordingly, a 7-byte message can be transferred by an 8-byte packet. The 18-byte message is divided into three packets (7+7+4). In the final packet, 3-byte dummy data is added on as padding.

15 The CPU 240 generates this packet in the RAM 226 (S701), sets the leading address thereof and the transfer length (18 bytes) thereof in the channel-0 register of the DMAC 241 (S702) and instructs the SCU 242 to start transmission (S703).

20 Data transfer is carried out by the SCU 242 and DMAC 241 (S704). When a prescribed number of data transfers have been completed, the DMAC 241 applies an interrupt to the CPU 240 (S705) and the CPU 240 executes post-processing (S706).

25 Transmission of the message is thenceforth repeated through the same procedure.

the same procedure.

09612571.070700

In the example set forth above, communication negotiation processing (determination of fixed packet length) is executed by the reader, though this
5 processing may be executed by the controller. However, in a case where a large number of structural elements have been connected to the system, executing the communication negotiation processing by the controller will take too much time. In such case it is preferred
10 that the processing be executed on the side of each of the connected elements. Further, it is possible for data send/receive processing on the side of the controller 110 also to be carried out through exactly the same procedure.

15 Thus, in accordance with the embodiment as described above, by adopting a scheme in which a variable-length message is transferred upon being divided into fixed-length packets, it is possible to combine and control a DMA controller and a communication
20 controller, thereby achieving high-speed data communication, even in a system not possessing a high-performance communication controller.

Further, depending upon the selection as to whether or not to implement a fixed-length packet scheme and the
25 method of deciding the upper-limit value of packet length by negotiation between devices at the time of

implements the functions of the embodiment by this processing.

It goes without saying that the present invention further covers a case where, after the program codes
5 read from the storage medium are written in a function expansion board inserted into the computer or in a memory provided in a function expansion unit connected to the computer, a CPU or the like contained in the function expansion board or function expansion unit
10 performs a part of or the entire process in accordance with the designation of program codes and implements the functions of the embodiment by this processing.

In a case where the present invention is applied to the above-described storage medium, program code
15 corresponding to the flowcharts (shown in Figs. 6A and 6B and/or Figs. 7A and 7B) described earlier would be stored on this storage medium.

Thus, in accordance with this embodiment as described above, it is possible to provide a method and
20 system for data communication between devices, wherein by adopting a scheme in which a variable-length message is transferred upon being divided into fixed-length packets, it is possible to combine and control a DMA controller and a communication controller, thereby
25 achieving high-speed data communication, even in a low-cost single-chip microcomputer.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that the invention is not limited to the specific
5 embodiments thereof except as defined in the appended claims.

09612571.070700

WHAT IS CLAIMED IS:

1. An image processing system comprising a combination of an image control unit and one or a plurality of image input/output units, wherein said image input/output unit and said image control unit are connected by communication means, said image control unit has first communication control means connected to said communication means, said image input/output unit has second communication control means connected to said communication means, and said system further includes control means for performing control so as to set predetermined communication conditions in said first and second communication control means at initialization, decide fixed packet length based upon mutually communicable packet lengths of packets exchanged via said communication means, set the decided fixed packet length in said first and second communication control means anew, and continue subsequent communication by DMA transfer in which a data string is divided into the set fixed packet lengths.
2. The system according to claim 1, wherein in a case where the data string is a variable-length message, said control means performs control in such a manner that a transmitting side adds information indicative of the end of a message onto a final packet when the variable-

length message is transmitted upon being divided into fixed-length packets, and a receiving side reproduces the original variable-length message after recognizing added-on final-packet information.

5 3. The system according to claim 1, wherein said control means includes first control means in said image control unit for controlling said first communication control means, and second control means in said image input/output unit for controlling said second
10 communication control means.

4. The system according to claim 3, wherein the decision of the fixed packet length is made by said first control means.

5. The system according to claim 3, wherein the
15 decision of the fixed packet length is made by said second control means.

6. The system according to claim 1, wherein the fixed packet length decided upon is whichever of the packet lengths of respective ones of said first and second
20 communication control means is smaller than an upper-limit value.

7. The system according to claim 1, wherein an image reading unit is connected as the image input/output unit and the system operates as an image reading system.

25 8. The system according to claim 1, wherein an image forming unit is connected as the image input/output unit

and the system operates as an image forming system.

9. The system according to claim 1, wherein an image reading unit and an image forming unit are connected as the image input/output units and the system functions as
5 an image input/output system.

10. The system according to claim 1, wherein start-stop synchronization serial communication means is used as said communication means, a serial communication controller and a DMA controller are combined as said
10 communication control means, the DMA controller transfers data by the fixed-length packets in accordance with a data transfer request from said serial communication controller and interrupts said image control unit when transfer of the fixed-length packet is
15 completed.

11. A system constructed by combining a plurality of devices and connecting them by communication means, wherein a first device has first communication control means connected to said communication means, a second
20 device has second communication control means connected to said communication means, and the system further includes control means for performing control so as to set predetermined communication conditions in said first and second communication control means at
25 initialization, decide fixed packet length based upon mutually communicable packet lengths of packets

exchanged via said communication means, set the decided fixed packet length in said first and second communication control means anew, and continue subsequent communication.

- 5 12. The system according to claim 11, wherein in a case where a data string is a variable-length message, said control means performs control in such a manner that a transmitting side adds information indicative of the end of a message onto a final packet when the variable-
10 length message is transmitted upon being divided into fixed-length packets, and a receiving side reproduces the original variable-length message after recognizing added-on final-packet information.

13. A data communication method in an image processing
15 system comprising a combination of an image control unit and one or a plurality of image input/output units, said image input/output unit and said image control unit being connected by communication means, wherein in a case where said image control unit has first
20 communication control means connected to said communication means and said image input/output unit has second communication control means connected to said communication means, said method comprises:

- an initial communication conditions setting step of
25 setting predetermined communication conditions in the first and second communication control means at

initialization;

a fixed packet length deciding step of deciding fixed packet length based upon mutually communicable packet lengths of packets exchanged via the

5 communication means; and

a fixed packet length setting step of setting the decided fixed packet length in the first and second communication control means anew and continuing subsequent communication by DMA transfer in which a data
10 string is divided into the set fixed packet lengths.

14. The method according to claim 13, wherein in the fixed-packet length deciding step, the fixed packet length decided upon is whichever of the packet lengths of respective ones of the first and second communication
15 control means is smaller than an upper-limit value.

15. The method according to claim 13, wherein after the fixed packet length has been set anew, communication is resumed upon elapse of a predetermined period of time.

16. The method according to claim 13, wherein start-
20 stop synchronization serial communication means is used as said communication means, a serial communication controller and a DMA controller are combined as said communication control means, the DMA controller transfers data by the fixed-length packets in accordance
25 with a data transfer request from said serial communication controller and interrupts said image

control unit when transfer of the fixed-length packet is completed.

17. A data communication method in a system constructed by combining a plurality of devices and connecting them
5 by communication means, wherein in a case a first device has first communication control means connected to said communication means and a second device has second communication control means connected to said communication means, said method comprises the steps of:

10 setting predetermined communication conditions in the first and second communication control means at initialization;

 deciding fixed packet length based upon mutually communicable packet lengths of packets exchanged via the
15 communication means; and

 setting the decided fixed packet length in the first and second communication control means anew and continuing subsequent communication.

18. The method according to claim 17, wherein in a case
20 where a data string is a variable-length message, a transmitting side adds information indicative of the end of a message onto a final packet when the variable-length message is transmitted upon being divided into fixed-length packets, and a receiving side reproduces
25 the original variable-length message after recognizing added-on final-packet information.

09612571.070700

19. A storage medium storing a computer-readable communication control program of an image processing system comprising a combination of an image control unit and one or a plurality of image input/output units, the
5 image input/output unit and the image control unit being connected by communication means, wherein in a case where said image control unit has first communication control means connected to said communication means and said image input/output unit has second communication
10 control means connected to said communication means, said communication control program includes:

an initial communication conditions setting step of setting predetermined communication conditions in the first and second communication control means at
15 initialization;

a fixed packet length deciding step of deciding fixed packet length based upon mutually communicable packet lengths of packets exchanged via the communication means; and

20 a fixed packet length setting step of setting the decided fixed packet length in the first and second communication control means anew and continuing subsequent communication by DMA transfer in which a data string is divided into the set fixed packet lengths.

25 20. The storage medium according to claim 19, wherein the communication control program includes a program in

said image control unit executed by a first control unit
for controlling said first communication control means,
and a program in said image input/output unit executed
by a second control unit for controlling said second
5 communication control means.

09642571.070700

ABSTRACT OF THE DISCLOSURE

09042571-070700

An image processing system comprising a combination of an image control unit and one or a plurality of image input/output units, wherein the image control unit and image input/output unit are connected by communication means. In a case where the image control unit has a first communication controller and the image input/output unit has a second communication controller, 10 predetermined communication conditions are set in the first and second communication controllers at initialization, a fixed packet length is decided based upon mutually communicable packet lengths of packets exchanged via the communication means, the decided fixed 15 packet length is set in the first and second communication controllers anew, and subsequent communication is continued by DMA transfer in which a data string is divided into the set fixed packet lengths. As a result, high-speed data communication is 20 achieved between units even in a low-cost single-chip microcontroller.




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B





FIG. 8

09612571.070700

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled _____

**METHOD AND SYSTEM FOR DATA
COMMUNICATION BETWEEN DEVICES**

the specification of which ☒ is attached hereto ☐ was filed on _____ as United States Application No. or PCT International Application No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

Country	Application No.	Filed (Day/Mo./Yr.)	(Yes/No) Priority Claimed
Japan	11-196498	July 9, 1999	Yes
Japan	2000-202361	July 4, 2000	Yes

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Application No.	Filed (Day/Mo./Yr.)	Status (Patented, Pending, Abandoned)
-----------------	---------------------	--

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

FITZPATRICK, CELLA, HARPER & SCINTO
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor HIDEYUKI MAKITANI

Inventor's signature _____

Date _____ Citizen/Subject of JAPAN

Residence 11-12-303, Honmachi 1-chome, Fuchu-shi
Tokyo, Japan

Post Office Address c/o Canon Kabushiki Kaisha,
30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, Japan

0612571.070700